

**LUBREX RED-2,** premium lubricating grease is designed for a wide variety of automotive, construction, chassis lubrication and industrial applications. It contains high quality mineral base oil and lithium complex thickener with EP additives, rust and oxidation inhibitors. As this grease uses a lithium complex thickener, it is structurally very stable and provides a longer life for grease.

## **PRODUCT FEATURES & BENEFITS**

- · Protection against wear
- · Protects equipment
- · Long grease life
- · Prevents leakage
- · Multifunctional capacity

## **APPLICATIONS**

- Automotive wheel bearings, chassis lubrication, highway and off highway applications
- Construction equipment, agricultural tractors, heavy duty transport and industrial greasing applications



NATIONAL LUBRICATING GREASE INSTITUTE CLASSIFICATION

**NLGI GC-LB** 



## **KEY PROPERTIES**

Parameter	Typical value	Method
Colour & Appearance	Red, translucent	Visual
NLGI Grade	2	-
Texture	Smooth	
Soap type / thickener type	Lithium Complex	-
Worked penetration @ 25°C, 60 strokes, mm/10	265 - 295	ASTM D217
Dropping point, min °C	245	ASTM D2265
Copper Corrosion, max	Negative	ASTM D4048

Note: This document does not constitute specifications of the product

ENVIRONMENT, HEALTH AND SAFETY - Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

All reasonable care has been taken to ensure that the information contained in this publication is accurate at the time of printing. However, the information is liable to variation in the event of subsequent changes in the blend, formulation, method of storage, improper handling and usage, etc.

for further information on LAUGFS lubricants products and services call the LAUGFS lube tech advisory service on 94 11 5565800 Monday to Friday.